



**STAUNCH**  
MACHINERY  
SINCE 1979

# STAUNCH Automatic Tire Inflator Machine HJ 921B JX



## Features

1. Preinstalled electron pressure display, safety, accurate and easy operation
  2. Manual discharge when over inflation
  3. Manual air inflation and measuring tire pressure with manual type
  4. Automatic air inflation with high speed and high level of accuracy
  5. Buzzing and lighting alarm appears after finishing inflation
  6. Tyre bead is not sealed with the tyre rim, the loose clamping mouth, the leakage pipeline and air leakage, all the situation above will lead to lighting and automatic alarm during the air inflation. And the inflator can proceed texting job three times at most. The inflator will not execute all the inflation order until the stoppages are absolutely removed.
- Adopting pressure sensor of high accuracy. accuracy2%(full scale reading)  
IP54 level waterproof design, which is attractive and durable.

## Technical Data

Model No.	HJ 921B JX
Voltage	220V 50/60Hz 1PH
Power	≤44W
Length of air inflator tube	Automatic Hose 9.5 meters
air inlet pressure	4~10bar /58~145PSI
inflation pressure	1~7bar /15~102PSI
tolerance for inflation pressure	±0.02 bar
working temperature	-20°C~70°C
relative humidity	10%RH~95%RH non-condensing
inflation speed	400L/Min(10Bar)
length scope of extending air pipe	not to exceed 13 meters